



REVISIONS				
REV	DESCRIPTION	DATE	INITIAL	APPROVED
1	REDRAWN FROM 1980 DILAPIDATED PRINTS.	4/10/08	WP	RW
2	ADDED -1 HEAT TREAT 28-32 RC AND CH'D MATERIAL FROM STRESS PROOF. CH'D ENGRAVE NOTE.	8/2/12	RJC	SE



ASSY QTY	ASSY QTY	B/O	PART #	UNIT QTY	DESCRIPTION	MATERIAL	B/O INFORMATION OR SPECIFICATIONS
			-3	1	ADAPTER	4140	3/8 X 2-1/2 X 2-1/2
		B/O		2	DOWEL PINS	HARDENED STEEL	Ø.187 x 3/4
	ASSY #						

 RED BARN MACHINE			
TITLE TORQUE WRENCH ADAPTER ASSEMBLY; FOUR BLADED TAIL ROTOR ASSY.			
DWG NO. RBD29826			REV 2
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCES ON: DECIMALS .XXX ± .005 .XX ± .01 .X ± .1 FRACTIONS ± 1/32 ANGLES ± 5°		DRAWN BY: PERRITT	
		APPROVED: <i>D. Weid</i>	
		HEAT TREAT: 28-32 RC	
		FINISH: BLACK OXIDE	
UNLESS OTHERWISE SPECIFIED 1. BREAK ALL SHARP EDGES 0.015 x 45° PR. 0.015 R 2. DIMENSIONAL LIMITS APPLY AFTER PLATING		SPEC	
		USED ON MODEL	
		MD	
SCALE NTS	DATE 4-10-08	SHEET 1 of 1	

REVISIONS				
REV	DESCRIPTION	DATE	INITIAL	APPROVED
--	--	--	--	--

			
TITLE			
<div style="text-align: center;">— —</div>			
DWG NO.			REV
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCES ON: DECIMALS .XXX ± .005 .XX ± .01 .X ± .1 FRACTIONS ± 1/32 ANGLES ± 5°			DRAWN BY: PERRITT APPROVED HEAT TREAT FINISH SPEC
UNLESS OTHERWISE SPECIFIED 1. BREAK ALL SHARP EDGES .015 x 45° PR. 015 R 2. DIMENSIONAL LIMITS APPLY AFTER PLATING		USED ON MODEL 	
SCALE	N.T.S.	DATE	8-15-07
		SHEET	1 of 1

